



Interplast Bore Hole Casings and Screens are produced to meet International standards. The joints are straight (flush threaded). Our trapezoid thread formation provides an easy, perfect and strong jointing system which allows joints to be removed and rejointed several times without causing any damage to the thread pitch.

Strict control of pipe wall thickness and diameter ensure thread uniformity. Different slot widths are available to satisfy the requirements of different rock formations.

No	DN	Inch	Outside Diameter (mm)	Thickness	Inside Diameter (mm)	Weight (kg/m)
1	100	4"	113	5.00	103.0	2.50
2	110	4"	110	6.00	98.0	2.85
3	115	4 ^{1/2} "	122	6.00	110.0	3.30
4	115	4 ^{1/2} "	125	5.00	115.0	2.95
5	115	4 ^{1/2} "	125	6.00	113.0	3.40
6	115	4 ^{1/2} "	125	6.50	112.0	3.80
7	115	4 ^{1/2} "	125	7.00	111.0	3.95
8	115	4 ^{1/2} "	125	7.50	110.0	4.20
9	115	4 ^{1/2} "	125	9.00	107.0	4.95
10	125	5"	140	6.50	127.0	4.15
11	125	5"	140	6.70	126.6	4.20
12	125	5"	140	7.00	126.0	4.40
13	125	5"	140	7.50	125.0	4.70
14	125	5"	140	8.00	124.0	4.99
15	125	5"	140	10.00	120.0	6.20
16	150	6"	160	7.50	145.0	5.60
17	150	6"	160	9.00	142.0	6.65
18	150	6"	165	7.50	150.0	5.80
19	150	6"	165	9.00	147.0	6.72
20	175	7"	196	8.50	179.0	7.65
21	200	8"	200	10.50	179.0	9.70
22	200	8"	200	11.50	177.0	10.35
23	200	8"	225	10.80	203.4	10.90
24	250	10"	250	11.90	226.4	13.35
25	250	10"	250	14.80	220.4	16.70
26	300	12"	315	15.0	285.0	21.15
27	300	12"	315	23.80	267.6	32.50
28	400	16"	400	19.10	361.8	34.00

Colour: **Blue.**

Sizes : **3m and 6m standard.**

Other sizes on request

Slot width (mm): 0.5, 0.75, 1.0, 1.5